

D70

SMART POS

Oldschool Vibes, Next-Gen Performance. Jam-Packed for Every Payment.

PCI PTS 6.x with SRED

Android 11 operating system

2.8" TFT Capacitive Touchscreen

3.8V/5000mAh battery

4G, WiFi (2.4GHz & 5G), Bluetooth® 5.0 connectivity

GPS, A-GPS, GALILEO, BEIDOU



Wi-Fi



Bluetooth



Android



4G Network



GPS



Printer



Camera

Specification

D70

OS	Android 11
Processor	Application CPU: 4*A53@ 2.0GHz Security CPU: 32-bit ARM 64MHz
Memory	2GB RAM, 8GB Flash 1GB RAM, 8GB Flash(Optional) 2GB RAM, 32GB Flash(Optional)
Display	2.8" 320 * 240 TFT Display Capacitive touchscreen
Indicator	N/A
Communications	4G/3G/2G WiFi: 802.11 a/b/g/n/ac, 2.4GHz&5G, Supports AP Bluetooth® 5.0
Satellite Positioning	GPS A-GPS GALILEO BEIDOU
Camera	2MP FF pixels
Audio	buzzer, speaker
Printer	Thermal printer Paper Roll Width: 58mm Paper Roll Diameter: 40mm
Magnetic Card Reader	Triple track, conforming to ISO 7810/7811/7813, Bi-directional swiping
EMV Card Reader	EMV L1/L2, conforming to ISO 7816, compliant Class A, B, C
Contactless Card Reader	EMV Contactless L1, conforming to ISO 14443 Type A/B, Mifare
Keys / Buttons	16 Keys: 0~9 5 Function Keys 1 Power ON / OFF
Certifications	PCI PTS 6.x with SRED EMV L1&L2, Contactless L1 Visa Paywave, MasterCard Paypass, Amex Expresspay, MIR Discover D-PAS, PCI PIN Security, MasterCard TQM CE, FCC, RoHS
Adapter/Power Supply	Input: 100-240V AC, 50Hz/60Hz Output: 5.0V DC, 2.0A
Battery	3.8V/5000mAh
Peripheral Ports	1 Type-C (OTG), 2 PIN POGO PIN 1 Micro SIM(option ESIM) + 1 Mini SIM(option SAM) + 1 Mini SAM 1 Micro SD Card Slot, Supports Up To 128 GB
Environmental Conditions	Operating temperature: 0°C~45°C Storage temperature: -20°C~60°C Relative humidity: 5%~95% (Non-condensing)
Dimensions	158mm x 75.2mm x 64.5mm, 368g(Including Battery)
Standard Accessories	1 Power adapter, 1 USB cable